

DN Series® 300

Lobby Monofunctional Cash Dispenser



With the highest cash capacity in the smallest footprint, the DN Series® 300 minimizes complexity and cost by design. Its compact and reliable architecture supports leaner, more agile self-service networks, unlocking new levels of efficiency, profitability and next-gen security while delivering a highly differentiated consumer experience.

The DM7V cash dispensing module delivers a powerful combination of capacity, precision, and reliability that sets a new benchmark in ATM technology. Its integrated, non-split module architecture ensures compactness without compromising functionality, while enabling faster serviceability and simplified component handling across the entire cash cycle.



More Personalized

Engaging, consistent, research-based design coupled with powerful Vynamic Marketing™ enables you to personally connect with consumers at the intersection of physical and digital channels.



More Integrated

A common platform supported by leading software and services ensures more seamless integration into your organization's channel ecosystem.



More Available

DN AllConnect™ Data Engine, an intelligent data-driven service architecture, maximizes the availability of the globally proven 6th generation dispensing module.



More Efficient

New functionality offers new opportunities to migrate transactions and engage consumers through the self-service channel.



More Future-Ready

Now you can offer cash dispense today and migrate to cash recycling tomorrow with the industry's most flexible self-service terminal in the smallest footprint.



More Sustainable

Built for a greener future: DN Series® minimizes power use, reduces service and CIT trips, and optimizes resources—supporting your sustainability goals at every step.



More Secure

Layered security features protect against traditional and emerging physical, data and cyber threats.



CROSS-PLATFORM MEDIA ENGINES**DM7V Engine (7th Generation Dispensing Module)**

- Dispense up to 60-note bundle
- Standard Dispensing Cassette: 420 mm note stacking capacity per cassette
- Dual Dispensing Cassette: 195 mm and 139 mm note stacking capacity for dispensing in one cassette
- Dispense 3 denominations, or up to 6 with dual cassettes in the standard version
- Dispense 4 denominations, or up to 8 with dual cassettes in the high capacity version
- Retract/reject cassette

ENHANCED SECURITY**Physical**

- Portrait, cash slot and environmental surveillance camera options
- Security Safes: UL 291 Level 1, CEN I, CEN III EX Gas, CEN IV EX Gas
- Variety of alarm options
- Electronic or mechanical safe locks
- Anti-cash-trapping sensor

Data

- Consumer awareness mirrors
- Encrypting PIN pad
- PIN pad shield
- Anti-skimming card readers
- Illuminated Privacy Panels

Cyber

- Trusted Device Communication
- Basic Endpoint Security
- CryptTA Stick secure service access
- Vynamic® Security
- Trusted Platform Module (TPM)
- AI enabled TILT Dispense Management to deter and minimize jackpotting loss

Display

- 15" with function keys and/or touchscreen
- 19" portrait or landscape touchscreen
- Vandal-resistant display
- Supports multi-touch
- Standard or high-bright LCD
- Privacy filter

Processor

- Intel® i5
- Intel® Active Management Technology (AMT)
- Solid state drives

Accessibility

- Compliant with regional height and reach requirements
- Audio options
- 2-way video camera/microphone
- User guide lights customizable with branding colors

ID Devices

- EMV motorized, dip, ActivEdge™ and/or contactless card readers
- Barcode scanner 1D/2D
- Fingerprint reader

Printers

- 80 mm thermal receipt printer
- Journal printer

Serviceability

- Front or rear load
- 10.1" service display on rear load systems
- Integrated with DN AllConnect Services™ Architecture

Platform Software & Operating System

- ProBase/C
- Windows®

Application Software

- Vynamic® Software

**Dimensions (HxWxD)**

1319 mm x 450 mm x 711 mm (UL)
[51.92 in x 17.71 in x 27.99 in] (UL)

1319mm x 450mm x 780 mm (CEN)
[51.92 in x 17.71 in x 30.70 in] (CEN)

See installation manual for other configurations and installation parameters.

*Components and technologies vary by region and are subject to availability